

Fork positioner with sideshift (FPSS)

Company		Contact
For new customers Postal address _____ Postal code _____ City _____ Country _____ VAT no. _____	Delivery address (if other) _____ _____ _____ _____ _____	For new contacts E-mail _____ _____ _____ Phone _____ Mobile _____

Forklift truck

Load capacity (kg)	Load centre distance (mm)	Overall width (mm)
_____	_____	_____
Machine type: Counterbalanced truck Reach truck Telehandler		
Manufacturer	Model name	(Model type/no.)
Mounting class: 2 3 4 5 A B		
Mast: Duplex w/o free lift Duplex w free lift Triplex w free lift Special:		
Mast code or drawing no.	Drawing will be sent	Fork carriage will be sent

Forks positioner

Width (mm)	Mounting type:	Integrated	Hook-on	Bracket/Quick coupler
C-series (C-profile) <u>Add-on</u> Over-centre (1 - 5 t) For Reach truck Tilt function Tilt cylinder		E-series (Pin-type) _____ For Reach truck Tilt function Tilt cylinder		F-/R-series (Roller mounted) <u>Add-on</u> Power pile slope

Forks and options (standard implies standard cross section and 1200mm length)

Standard	Other (mm):	Length	Width	Thickness	Load Backrest
Fork carriers (lower bolted hooks)	Carrier plates (lower quick release hooks)	QC-6 (TWS) (Quick coupling system)	Hook-on fork (TWS)	HCB™-camera SideCam FrameCam	SmartFork® Specify which cameras and sensors.
K00I-reachforks®	RG2	RG4	Other	Lift-Drop fork	ISO-fork 2 3 4 5 A B
1100/750 mm	1200/850 mm	1350/1000 mm	Other		Class

Additional information