




## MANUAL QUICK COUPLER

### FEATURES

- Functions as a quick coupler
- Redirects hydraulic functions
- Adapted with alternative quick couplings



Multifaster

With **CarryAll™**, you get a flexible attachment that can be adapted to your needs. The system makes it easy to switch between different hook-on forks, hook-on positioners and attachments — including those with hydraulic functions.

CarryAll™ is a system consisting of adapters integrated into the frame for manual mounting of various tools, as well as four hydraulic quick couplings (manual 6/2 valves) that manage two hydraulic functions.

With this setup, the fork positioner can carry everything from forks to clamps, rotators, and other equipment with active functions. Depending on capacity, you can choose between different ISO classes or TWS hooks (Terminal West Suspension) for the adapters.

Changing between fork lengths takes approximately 10 minutes, while mounting and connecting a hook-on attachment takes around 15 minutes. If you need to switch between different fork lengths or attachments one to two times per day or more, and want to further enhance workplace safety, our automatic quick-couplers OQT are an excellent alternative.

### ADAPTIONS

Instead of manual 6/2 valves, the unit can be equipped with Multifaster or any other quick-connection solution upon request.

### ADAPTERS AND QUICK COUPLINGS

Capacity: 1 000 - 18 000 kg



Model	Capacity (kg) / LC (mm)	Width CarrierPlate (mm)	Class ISO 2328 / TWS
CA, C12-25	2500 / 500	100	2
CA, C35	3500 / 500	125	2,3
CA, C50	5000 / 500	125	3
CA, C50E-60	6000 / 600	150	3,4
CA, C70-C80	8000 / 600	150	4
CA, C80E	8000 / 900	150	4
CA, C80X	8000 / 1100	200	4
CA, E2-20/25	2500 / 500	100	2
CA, E3-30/35	3500 / 500	125	2,3
CA, E4-50	5000 / 500	125	3
CA, E4-50E-60	6000 / 600	150	3,4
CA, E4-70-80	8000 / 600	150	4
CA, E4-80E	8000 / 900	150	4
CA, F4-60	6000 / 600	150	3,4
CA, F4-80	8000 / 600	150	4
CA, F4-120	8000 / 900	150	4
CA, F4-140	8000 / 1100	200	4
CA, RHD-100	10 000 / 600	200	4
CA, RHD-120	12 000 / 600	200	TWS
CA, RHD-140	14 000 / 600	200	TWS
CA, RHD-150	15 000 / 600	200	TWS
CA, RHD-160	16 000 / 600	200	TWS
CA, RHD-180	18 000 / 600	200	TWS
CA, RHD-180E	18 000 / 900	250	TWS
CA, RHD-100X	10 000 / 1200	200	TWS
CA, RHD-120X	12 000 / 1200	200	TWS
CA, RHD-140X	14 000 / 1200	250	TWS
CA, RHD-150X	15 000 / 1200	250	TWS
CA, RHD-160X	16 000 / 1200	250	TWS

#### NOTE

Incl. CarrierPlates with quick release hooks, 2 valves, and 4 hydraulic quick couplings. Forks not included.

All capacities up to 11 tonnes can be offered with ISO or TWS suspension.

Capacities exceeding 11 tonnes are offered with TWS-suspension.